

D320 SERIES

Tunable RF Driver



902

The D320 family of drivers are electronically tunable, On-Off gated RF generators. They are designed for use with the ISOMET 1201, 1205, 1206 and 1207 Acousto-Optic Bragg cells for the simultaneous deflection and intensity modulation of a laser beam.

Contained in each driver is a varactor tuned oscillator, a fast acting digitally controlled RF switch, and a class-A power amplifier. The oscillator features good tuning linearity and a fast slew rate. Although not temperature stabilized, the oscillator frequency stability is satisfactory for many linear scan applications. The modulation input is TTL compatible. It has a 10-90% switching time (rise time) of 5ns.

The D320 series is also offered with the modulation input modified to accept a +0 to +2 Volt unipolar signal for amplitude control. This option is offered at a nominal additional cost and is indicated by adding a "788" suffix.

SPECIFICATIONS

Oscillator Type:	Varactor tuned, Emitter coupled transistor
Amplifier Type:	Broadband Class A
Output RF Power:	≥ 1.0W
Output Impedance:	50Ω (Nominal)
Load VSWR:	< 2.5:1 for best results
Output RF Power Variation vs. Frequency:	≤ 1dB
Spurious Outputs:	Harmonics > 20dB below fundamental
Tuning Characteristics:	Linear frequency vs. tuning voltage
Tuning Voltage:	≅ +4V to +17V
Tuning Linearity:	± 1% from best fit straight line over specified tuning range
Tuning Voltage Impedance:	Drive from low impedance source, 50Ω or less
Tuning Slew Rate:	> 10MHz/μs
Residual FM:	< 10KHz peak to peak
Frequency Stability:	± 0.25% from 0° to +60°C
Modulation Input:	TTL Compatible, Positive Logic RF on ≥ +2.75V; RF Off ≤ +0.3V
Digital Input Impedance:	50Ω Source or TTL Line Driver
RF On-Off Ratio:	40dB
DC Power Input:	+28VDC at 600mA Regulated to ± 0.25%
Temperature Range:	0°C to 60°C Ambient, temperature at Mounting Face must not exceed 70°C
Mounting Orientation:	Any
Dimensions:	See Outline (reverse side)

<i>MODELS</i>	<i>D321</i>	<i>D322B</i>	<i>D323B</i>
Frequency Range	30-50MHz	57-103MHz	82-138MHz
Scale Factor	2MHz/V	3MHz/V	4MHz/V

ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

ISOMET CORP, 5263 Port Royal Rd, Springfield, VA 22151, USA.

Tel: (703) 321 8301 Fax: (703) 321 8546


E-mail: ISOMET@ISOMET.COM Web Page: WWW.ISOMET.COM

Quality Assured.

In-house: RF & Digital design

Software Development

OEM manufacture





D320 SERIES

Tunable RF Driver



902

OUTLINE DRAWING



ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

ISOMET CORP, 5263 Port Royal Rd, Springfield, VA 22151, USA.

Tel: (703) 321 8301 Fax: (703) 321 8546

E-mail: ISOMET@ISOMET.COM Web Page: WWW.ISOMET.COM

Quality Assured.

In-house: RF & Digital design

Software Development

OEM manufacture