



1. MUST WITHSTAND 15KV DC FOR ONE MINUTE AT 8,500 FT.

1. TOLERANCES:
FRACTIONS $\pm .010$ DECIMALS $\pm .004$ ANGLES $\pm 0^{\circ} 30'$
T. I. R. CONCENTRICITY OF ANY 2 DIAMETERS MAY NOT
EXCEED THE SUM OF THEIR TOLERANCES.

2. REMOVE ALL BURRS. BREAK SHARP EDGES .005 MAX.
3. NO FILLETS PERMITTED.
4. SURFACE ROUGHNESS 63 MICROINCHES RMS MAX.
5. ALL DIMENSIONS PRIOR TO PLATING.

ITEM	REQ'D	DESCRIPTION	DRAWING NO.	
				1064-2

REVISIONS	
ISSUE	CHANGES

SPEC.

**BULKHEAD
RECEPTACLE**

DRAWN	AME	DATE	30 DEC 68
-------	-----	------	-----------

APPR. 12/75	DATE 4 DEC 68
-------------	---------------

KINGS ELECTRONICS
40 MARBLEDALE ROAD
TUCKAHOE, N. Y. 10707

1064-2

DIETZGEN 198M Ageproof Tracing Vellum 8515

S-D